SRGM-CL



SRGM-CL GENERAL FEATURES

- Welded steel construction
- High carbon/high chrome, two edged top and four edged bottom blades
- Cutting beam working in perfectly sliding, durable teflon slideways
- Easy blade gap adjustment in front
- Mechanical sheet clamping system
- Can be integrated to Cut-to-Length Line Systems

DIRECT-GEAR MOTORISED GUILLOTINES FOR CUT-TO-LENGTH LINES

SRGM–CL STANDARD EQUIPMENT

- Squaring arm with T-slot, stopper and ruler
- Front sheet holding arms
- Finger protection cages
- Table with ball transfer
- Cutting line illumination with shadow wire

SRGM–CL OPTIONAL EQUIPMENT

- Electrical box
- Rear protection cages with photocell
- Rear protection cages with light barrier



SRGM–CL MODELS

MODEL	SHEARING CAPACITY	MAX. SHEARING LENGTH	STROKES PER MINUTE	MOTOR POWER	TABLE HEIGHT	TABLE WIDTH	WIDTH	LENGTH	HEIGHT	WEIGHT
	mm	mm	cuts/min	kW	mm	mm	mm	mm	mm	kg
SRGM-CL 1100	6.0	1100	31	7.5	800	455	1250	1750	1400	1900
SRGM-CL 1360	6.0	1360	31	7.5	800	455	1250	2050	1400	2200
SRGM-CL 1560	5.0	1560	31	7.5	800	455	1250	2250	1400	2400
SRGM-CL 2060	4.0	2060	31	7.5	800	455	1250	2700	1400	2900