SRGM-H



SRGM-H GENERAL FEATURES

- Welded steel construction
- High carbon/high chrome, two edged top and four edged bottom blades
- Cutting beam working in perfectly sliding, durable teflon slideways
- Mechanical sheet clamping system

DIRECT - GEAR MOTORISED GUILLOTINES (LIGHT TYPE)

SRGM-H STANDARD EQUIPMENT


- Manual back gauge with 750 mm stroke
- Squaring arm with ruler
- Foot pedal
- Cutting unit counter
- Front sheet holding arms
- Finger protection cages
- Rear protection cages with photocell
- Table with ball transfer
- Cutting line illumination with shadow wire

SRGM-H OPTIONAL EQUIPMENT

- Servo motor for high speed & high accuracy backgauge
- BRL 401.2 NC control unit
- 7" touch-screen NC control unit
- NC controlled back gauge with 750 mm stroke
- NC controlled back gauge with 1000 mm stroke
- Pneumatic sheet support system with Return-to-Rear feature
- Rear protection cages with light barrier
- 0-180° angular cutting device
- Longer squaring arm and front sheet holding arms up to 3000 mm
- Front operated manual back gauge with ball screw (1100, 1360 & 1560)







SRGM-H MODELS

MODEL	SHEARING CAPACITY	MAX. SHEARING LENGTH	STROKES PER MINUTE	MOTOR POWER	TABLE HEIGHT	TABLE WIDTH	WIDTH	LENGTH	HEIGHT	WEIGHT
	mm	mm	cuts/min	kw	mm	mm	mm	mm	mm	kg
SRGM-H 1100	3.0	1100	35	3.0	810	390	2100	1720	1260	1100
SRGM-H 1360	3.0	1360	35	3.0	810	390	2100	1920	1260	1250
SRGM-H 1560	3.0	1560	35	3.0	810	390	2100	2100	1260	1500
SRGM-H 2060	3.0	2060	35	4.0	810	390	2100	2650	1260	1750
SRGM-H 2560	2.5	2560	35	4.0	810	390	2100	3150	1260	1950
SRGM-H 3060 *	3.0	3060	31	7.5	810	455	2100	3650	1260	3000

* Easy blade gap adjustment in front, Table with ball transfer