IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com

MACHINE MODEL

BS 300 PLUS SHI

Semiautomatic bandsaw for small, medium production

Short description

BS 300 PLUS SHI is the semiautomatic bandsaws intended to cut both left (up to 60°) and right (from 0° to 45°). The machine is a suitable working tool for small and medium batch production for mechanics and steelwork.


Scan the video



Cutting capacity at 90°	Round 255 mm. Square 230 mm. Rectangular 300x180mm
Cutting capacity at 45° right	Round 210 mm. Square 190 mm. Rectangular 200x180mm
Cutting capacity at 45° left	Round 180 mm. Square 160 mm. Rectangular 180x100mm
Cutting capacity at 60° left	Round 135 mm. Square 110 mm. Rectangular 130x100mm
Cutting capapcity with bundle device	250x130mm - 85x10mm
Maximum capacity for full materials	180mm
Blade size.	2765x27x0,9
End-cutting bandsaw inclination	3°
Blade motor	1,5/1,8 kw
Blade speed	35/70 - 15÷110 m/min
Hydraulic unit motor power	kw 0,37
Hydraulic united tank	Lt 12
Coolant tank	Lt 20
Size - Weight	1230x1700x1750 mm - 412kg
Working table height	940 mm
Blade tension	1700 kgf/cm2


IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com

Features



Wide working area

BS 300 PLUS is equipped with a wide diameter working area and a system of automatic easy stops at 0°, 45° and 60° left and 45° right with graduated plate to identify and set different angles.



Opening vice

The vice has adjustable guides, free to move alongside the worktable, with rapid approaching and camping.



Rigid sawframe


Machine sawframe is rigid cast-iron with tubolar section, 320 mm pulleys, high blade tension at 1700 kg/cm2 and to avoid an excessive strain on the blade with frontal regulation and microswitch conroller.



Blade protection

A carter protect che blade, allowing to have easy access for maintentance when needed; a system with blade guides with hard pads, additional lateral bearings provides for the perfect allignment of the blade

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Easy to use

Safe starting through the button on the handle with warning light to inform the use about the correct machine functioning. Coolant-tank and electropump are placed inside the floor stand.



Electromic inverter — OPTIONAL

Art. A-0001

If required, the electronic inverter for variable blade speed allows the operator via keyboard to adjust the machine to be able to cut a wide range of materials and different sections. The change of speed is via inverter and it does not affect the power of the engine even at low speeds.



Minimal lubrification system — OPTIONAL

Art. 000947-13

It is possible to require , for all Imet machines, the minimal lubrication system , it avoids the dispersion of refrigerant liquid typical in the use of emulsifiable oil, the life of the blade is not in any way affected.



Adapter to synchonize RTP/RTD — OPTIONAL

Art. 000910-09

Adapter to synchronize the RTP/RTD table with sawframe motion

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Laser ray — OPTIONAL

Art. A-0003


Laser ray (not compatible with bundle device)



Pressure reducer — OPTIONAL

Art. 000965

Pressure reducer for hydraulic vice (only for SHI version)



Hydraulic device for bundle cutting — OPTIONAL

Art. X000951-03

Only for SHI version, hydraulic device for bundle cutting (Max 250x130mm - Min 85x10mm).




Foot pedal — OPTIONAL

Art. 000970

Foot pedal with 3 3m long cable (only for SHI version).


IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Adjustable foot for floor fixing — OPTIONAL

Art. 000918-01

Adjustable foot for floor fixing (4 pcs. required)



Connection element for unloading table — OPTIONAL

Art. RAB2PS

Connection element for unloading table equipped with 1 roller ans a slide to collect coolant.



Loading/unloading table - first element — OPTIONAL

Art. RTSPRW30

Loading/unloading roller table, first element, 2 m long, maximum capacity 700kg




Loading/unloading table - following element — OPTIONAL

Art. RTSSEW30

Loading/unloading roller table, 2m long, following element, maximum capacity 600kg


IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



RM measuring system - first element OPTIONAL

Art. RMPRW3050

RM measuring system, to be installed on RTS W3050 roller tables, with millimeter scale and mechanical stop, 1st element, 2 m



RM measuring system - following element OPTIONAL

Art. RMSEW3050

RM measuring system, to be installed on RTS W3050 roller tables, with millimeter scale, following element, 2 m



Unloading table with digital reading OPTIONAL

Art. RTD

RTD2LW30 - unloading table with digital reading and manual posioning, mesurement length 2m, capacity 700kg RTD4LW30 - unloading table with digital reading and manual posioning, mesurement length 4m, capacity 1300kg RTD6LW30 - unloading table with digital reading and manual posioning, mesurement length 6m, capacity 1900lg



Unloading table with motorized length stop OPTIONAL

Art. RTP

RTP2W30 - Unloading table with motorizedn length stop and selection of the lengths via keayboad, 2m, 700kg. RTP4W30 - Unloading table with motorizedn length stop and selection of the lengths via keayboad, 4m, 1300kg. RTP6W30 - Unloading table with motorizedn length stop and selection of the lengths via keayboad, 6m, 1900kg.

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Pair of vertical roller — OPTIONAL

Art. RI-W30

Pair of vertical rollers 300 mm made in steel, max 2 pairs for each element 2m long. To use without rollers covers.