IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com

MACHINE MODEL


KS 620

Semiautomatic bandsaw for steel constructions

Short description

The KS saws are the only ones in their class that can cut 60 ° right and left by positioning the locking vice only once. The vice is sliding transversely on the support surface with locking and rapid approach.


Scan the video



Cutting capacity at 0°	Round: 500mm - Square: 420mm - Rect.: 620x330mm/620x310 (without MQL)
Cutting capacity at 45° left/right	Round: 445mm - Square: 410mm - Rectangular: 390x440mm
Cutting capacity at 60° left	Round: 320mm - Square: 290mm - Rectangular: 250x355mm
Cutting capacity at 60° right	Round: 245mm - Square: 240mm - Rectangular: 250x355mm
Cutting capacity (BUNDLE)	Max: 500x300mm - Min: 160x40mm
Cutting capacity at 0° solids (C45)	250mm
Blade size	5320x34x1.1mm
Blade speed	15-100m/min
Blade	3KW
Working table height	805mm
Blade inclination	6°
Weight	1450kg
Dimensions	1705x2500x2500mm
Blade tension	2000 kgf/cm2


IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com

Features




Vice and material locking

The vice slides transversally on the work surface, linear guides, locking and rapid approach, complete with standard pressure reducer. All the saws of KS series (450, 502, 620 and 652) allow to fix the material clamping vice only once and then to rotate the arc for cutting both right and left (up to 60 °). The vice is equipped with a pressure regulator positioned on the hydraulic unit.



Large working table

Easy to use thanks to the rotating work surface integral with the arc and the blade passage to optimize the material support system during processing in all angles.



Cutting precision

The cutting precision is ensured by the graduated scale (on the work surface) which constitutes a visual reference for the operator in case of angle cutting. There're also automatic stops at 45°left, 0 ° and 45 ° right. To increase cutting precision, IMET band saws are equipped of a system for detecting degrees of cut away from the center.



Steelframe and blade inclination


In electro-welded steel, the blade has an inclination of 6 ° to improve the penetration in the material and optimize the execution of the cut. The rotation of the arc is done by bearing preloaded. The blade of KS 620 has a tensionning of 2000kgf/cm2 and is equipped with a control microswitch for immediate stop in case of blade breaking or power failure.

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Inclinated blade

KS 620 and all the saws of the KS range finish the cut with the blade inclined 6 °, facilitating the penetration of the blade into the material and allowing to always cut a section of material even in presence of a solid.



Material detection device

To facilitate the approach of the blade to the material KS450 mounts a device for detection automatic cutting start and end point. The machine offers the opportunity to remove the device if you want to increase the cutting capacity at 0 ° and 45 ° (right and left).



Blade cleaning

Motorized nylon cleaning brush for blade, driven by motor pulley to always keep in perfect condition the cutting blade.



Control panel

KS 620 is equipped with a mobile control console with control LED for tensioning the blade, opening of the blade guard, motor thermal block and electrical tension. Through the coontrol the operator can choose between 3 different ways of cutting end: ascent of the bow with stopped blade, ascent of the bow with blade in movement and end of cycle without bow ascent.

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Laser



Minimal lubrication system OPTIONAL

Art. 000947-09


The lubrication system cancels the dispersion of the coolant without damaging or affecting the life of the blade. The system is equipped with a 1.3l tank and nozzle.



Angle display OPTIONAL

Art. A-0004

It is possible to view the cutting angle and optimize the work process thanks to the visualization via LCD display.



Hydraulic device for bundle cutting OPTIONAL

Art. 000951-07

Hydraulic device for bundle cutting Max: 500x300mm - Min: 160x40mm

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Loading/unloading roller table — OPTIONAL

Art. RTSKS600

Roller conveyor suitable for the unloading and loading side. Length 1.5m, 1 pedestal, max loading 1500kg.



Unloading roller table — OPTIONAL

Art. RTL


Unloading roller table with digital reading and manual movement. Available : -RTL3KS600 Measuring lenght of 3m, 3 pedestals, max loading 3000kg; -RTL6KS600 Measuring lenght of 6m, 5 piedestals, max loading 6000kg.



Unloading roller table — OPTIONAL

Art. RTP

Unloading roller table with length stop and selection of the lengths by means of a keyboard Available: -RTP3KS600 Measuring lenght of 3m, 3 pedestals, max loading 3000kg; -RTP6KS600 Measuring lenght of 6m, 5 piedestals, max loading 6000kg.



Motorized loading roller table — OPTIONAL

Art. RTR LOADING

Loading motorised roller tables, with chain transmission and motor reducer managed by inverter, with mobile keyboard. Available : -3m, loading 3000kg; -6m, loading 6000kg; -9m, loading 9000kg; -12m, loading 12000kg.


IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Motorized unloading roller table — OPTIONAL

Art. RTR UNLOADING


Unloading motorized roller table, with chain transmission and motor reducer managed by inverter, available only together with loading roller table. Available: -3m, loading 3000kg; -6m, loading 6000kg; -9m, loading 9000kg; -12m, loading 12000kg.



Digital reading length stop — OPTIONAL

Art. RL

Digital reading length stop with manual positioning with automatic slowdown sensors, available only together with unloading motorized roller table - Measuring lenght 3m; Measuring lenght 6m; Measuring lenght 9m; Measuring lenght 12m



Motorized lenght stop — OPTIONAL

Art. RR

Numerical control motorized measurement RR with fast approching for automatic slowdown of the piece (to be ordered coupled with automatic conveyors) -RR6S 6m measuring lenght -RR9S 9m measuring lenght -RR12S 12m measuring lenght



Vertical rollers — OPTIONAL

Art. RI-W60

Pair of containment vertical rollers, made in steel, max 2 pairs for each element 1,5 mt long.

IMET SPA
Località tre fontane, 6 - 24034
Cisano Bergamasco (BG) Italy
Tel +39 035 4387911 | Fax +39 035 787066
imet@imetsaws.com
www.imetsaws.com



Single vertical roller OPTIONAL

Art. RI-300

Single vertical roller, height of 250 mm. to prevent falls, max 2 each 1,5 mt.